t2

Refined hydration. Digital precision.

Overview

— Next-generation integrated tap
— Refined hydration
— Ultra-compact, durable ProCore®
— Digital precision
— Energy-efficient
— Easy-to-fit ventilation kit
— Advanced UV protection built-in
— Bluetooth® Alarmed Waste Kit
— Totality® is our unique methodology designed to ensure our appliances provide an exceptional standard of hygiene.

Specifications

Chilled temperature - **2°C**
ProCore+ chilled & sparkling capacity - **80L/h**
ProCore chilled & sparkling capacity - **50L/h**
Dispense height - **310**
Tap height - **390**

Accessories

500ml water bottles
Printed paper cups 463428
Install kit with 3M filter 461202
Refill station cabinet 601604

T2 ProCore W320xD375xH335mm

Dispense Options	Water system	Max power consumption	Black	Steel	Black LED-UV	Steel LED-UV
Chilled & Ambient	Dry Chill®	140W	742000	742010	742020	742030
Chilled & Sparkling	Dry Chill®	200W	742080	742090	742100	742110
Chilled, Ambient & Sparkling	Dry Chill®	200W	742160	742170	742180	742190

T2 ProCore+ W320xD375xH350mm

Dispense Options	Water system	Max power consumption	Black	Steel	Black LED-UV	Steel LED-UV
Chilled & Ambient	Dry Chill®	140W	742240	742250	742260	742270
Chilled & Sparkling	Dry Chill®	200W	742320	742330	742340	742350
Chilled, Ambient & Sparkling	Dry Chill®	200W	742400	742410	742420	742430

Simple-fit Ventilation Base
W322xD431xH60mm
(Includes 20mm overhang)

borg&
overström

Find out more:
https://www.borgandoverstrom.com/en/p/tap-systems/t2/